

Product Number: 49467

Order Abbreviation: QHE 4X32T8/347 ISN-SC

General Description: 4-lamp 32wT8 High Efficiency Instant start electronic ballast, 347V, normal ballast factor, 10-pk

Product Information

Abbrev. With Packaging Info.	QHE4X32T8347ISNSC 10/CS 1/SKU
Ballast Factor	0.88
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6810
Circuit Type	Parallel
Family Brand Name	QUICKTRONIC High-Efficiency
Input Current (Amps)	0.00
Nominal Voltage (V)	347V
Number of Lamps	4
Open Circuit Voltage (V)	<600V
Power Factor	>0.97
Primary Lamp Type	FO32/XP
Sound Rating	A
Starting Method	Instant start
Starting Temperature - Fahrenheit	-20
Starting Temperature - Celsius	-29
Total Harmonic Distortion (THD)	<10%
Wiring Method	Leads
Max Case Temperature	70°C

Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 18 feet

- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Insulate unused leads
- Ground ballast case
- Lampholder must be shorted per diagram
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Wiring diagram applies to instant start standard, low power (LP), PLUS, and HD10 ballast types.
- High power factor
- Minimum starting temperature: 60 F / 16 C with SS lamps
- Minimum starting temperature: -20 F / -29 C
- FCC 47 CFR part 15, Class A
- Insulate unused leads individually for 600V