



UPC Code : 078477320259

Country Of Origin : Mexico



830-E

30 Amp, 125 Volt, NEMA TT-30P, 2P, 3W, Plug, Straight Blade, Industrial Grade, Angle, Grounding - Black

Leviton offers a large selection of 15, 20, 30 and 50 Amp Commercial Grade Straight Blade Plugs and Connectors, available in a wide variety of features. These rugged performers are moisture, chemical and abuse-resistant. And they're ideal for indoor and outdoor use. Our EPTR rubber-backed plugs and connectors stand up to rough use, protecting against dirt and moisture. The deep-slotted, backed-out terminal screws draw backwire clamps securely over stripped leads for maximum conductivity.

****This is a direct replacement of 830-T**

Technical Information

AC Horsepower Ratings

At Rated Voltage : 2 HP

Electrical Specifications

Amperage : 30 A

Current Limiting : Full Rated Current

Dielectric Voltage : Withstands 2000V per UL498

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C after 50 cycles OL at 150 percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Operating Temperature : -40°C to 60°C

Material Specifications

Assembly Screws : Steel, Zinc Plated

Blades/Contacts : Brass

Body Material : Thermoplastic

Color : Black

Mechanical Specifications

Cord Range : .687 - .875

Product ID : Ratings are permanently marked on device

Terminal Accom. : 10 AWG

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Product Features

Color : Black

NEMA : TT-30P

Warranty : 2-Year Limited

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File 152105

NEMA : WD-6

NOM : 057

UL498 : File E13399

Warranty : 2-Year Limited

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

